



A Well Balanced Finite Volume Kinetic (FVK) scheme for unsteady mixed flows in non uniform closed water pipes.

Mehmet Ersoy¹, Christian Bourdarias² and Stéphane Gerbi³

Laboratoire de Mathématiques, Clermont Ferrand, March 31, 2011

-
1. BCAM, Spain, mersoy@bcamath.org
 2. LAMA-Savoie, France, christian.bourdarias@univ-savoie.fr
 3. LAMA-Savoie, France, stephane.gerbi@univ-savoie.fr

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK


- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

UNSTEADY MIXED FLOWS IN CLOSED WATER PIPES ?


- Free surface area (SL)

sections are not completely filled and the flow is **incompressible**...




UNSTEADY MIXED FLOWS IN CLOSED WATER PIPES ?

- Free surface area (SL)
sections are not completely filled and the flow is incompressible. . .
- Pressurized area (CH)
sections are non completely filled and the flow is **compressible**. . .



UNSTEADY MIXED FLOWS IN CLOSED WATER PIPES ?

- Free surface area (SL)
sections are not completely filled and the flow is incompressible. . .
- Pressurized area (CH)
sections are non completely filled and the flow is compressible. . .
- Transition point



EXAMPLES OF PIPES



Orange-Fish tunnel



Sewers ... in Paris



Forced pipe



problems ... at Minnesota

<http://www.sewerhistory.org/grfx/misc/disaster.htm>

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

PREVIOUS WORKS

FOR FREE SURFACE FLOWS :


GENERALLY

Saint-Venant equations :

$$\begin{cases} \partial_t A + \partial_x Q = 0, \\ \partial_t Q + \partial_x \left(\frac{Q^2}{A} + g I_1(A) \right) = 0 \end{cases}$$

with

$A(t, x)$:	wet area
$Q(t, x)$:	discharge
$I_1(A)$:	hydrostatic pressure
g	:	gravity



Advantage

- Conservative formulation → Easy numerical implementation



Hamam and McCorquodale (82), Trieu Dong (91), Musandji Fuamba (02), Vasconcelos *et al* (06)

PREVIOUS WORKS

FOR **PRESSURIZED** FLOWS :

GENERALLY

Allievi equations :

$$\begin{cases} \partial_t p + \frac{c^2}{gS} \partial_x Q = 0, \\ \partial_t Q + gS \partial_x p = 0 \end{cases}$$

with

$p(t, x)$:	pressure
$Q(t, x)$:	discharge
$c(t, x)$:	sound speed
$S(x)$:	section

Advantage

- Compressibility of water is taken into account \Rightarrow Sub-atmospheric flows and over-pressurized flows are well computed

Drawback

- Non conservative formulation \Rightarrow Cannot be, at least easily, coupled to Saint-Venant equations



Winckler (93), Blommaert (00)


PREVIOUS WORKS

FOR MIXED FLOWS :

GENERALLY

Saint-Venant with Preissmann slot artifact :

$$\begin{cases} \partial_t A + \partial_x Q = 0, \\ \partial_t Q + \partial_x \left(\frac{Q^2}{A} + g I_1(A) \right) = 0 \end{cases}$$



Advantage

- Only one model for two types of flows.

Drawbacks

- Incompressible Fluid \implies Water hammer not well computed
- Pressurized sound speed $\simeq \sqrt{S/T_{\text{fente}}}$ \implies adjustment of T_{fente}
- Depression \implies seen as a free surface state



Preissmann (61), Cunge *et al.* (65), Baines *et al.* (92), Garcia-Navarro *et al.* (94), Capart *et al.* (97), Tseng (99)

OUR GOAL :

- Use Saint-Venant equations for free surface flows


OUR GOAL :

- Use Saint-Venant equations for free surface flows
- Write a pressurized model
 - ▶ which takes into account the compressibility of water
 - ▶ which takes into account the depression
 - ▶ similar to Saint-Venant equations

OUR GOAL :

- Use Saint-Venant equations for free surface flows
- Write a pressurized model
 - ▶ which takes into account the compressibility of water
 - ▶ which takes into account the depression
 - ▶ similar to Saint-Venant equations
- Get one model for mixed flows

To be able to simulate, for instance :



C. Bourdarias and S. Gerbi

A finite volume scheme for a model coupling free surface and pressurized flows in pipes.
J. Comp. Appl. Math., 209(1) :109–131, 2007.

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

DERIVATION OF THE FREE SURFACE MODEL

3D INCOMPRESSIBLE EULER EQUATIONS

$$\begin{aligned}\rho_0 \operatorname{div}(\mathbf{U}) &= 0 \\ \rho_0 (\partial_t \mathbf{U} + \mathbf{U} \cdot \nabla \mathbf{U}) + \nabla p &= \rho_0 F\end{aligned}$$

Method :

- 1 Write Euler equations in curvilinear coordinates.
- 2 Write equations in non-dimensional form using the small parameter $\epsilon = H/L$ and takes $\epsilon = 0$.
- 3 Section averaging $\overline{U^2} \approx \overline{U} \overline{U}$ and $\overline{UV} \approx \overline{U} \overline{V}$.
- 4 Introduce $A_{sl}(t, x)$: wet area, $Q_{sl}(t, x)$ discharge given by :

$$A_{sl}(t, x) = \int_{\Omega(t, x)} dydz, \quad Q_{sl}(t, x) = A_{sl}(t, x)u(t, x)$$

$$u(t, x) = \frac{1}{A_{sl}(t, x)} \int_{\Omega(t, x)} U(t, x) dydz$$

DERIVATION OF THE FREE SURFACE MODEL

3D INCOMPRESSIBLE EULER EQUATIONS

$$\begin{aligned}\rho_0 \operatorname{div}(\mathbf{U}) &= 0 \\ \rho_0 (\partial_t \mathbf{U} + \mathbf{U} \cdot \nabla \mathbf{U}) + \nabla p &= \rho_0 F\end{aligned}$$

Method :

- 1 Write Euler equations in curvilinear coordinates.
- 2 Write equations in non-dimensional form using the small parameter $\epsilon = H/L$ and takes $\epsilon = 0$.
- 3 Section averaging $\overline{U^2} \approx \overline{U} \overline{U}$ and $\overline{UV} \approx \overline{U} \overline{V}$.
- 4 Introduce $A_{sl}(t, x)$: wet area, $Q_{sl}(t, x)$ discharge given by :

$$A_{sl}(t, x) = \int_{\Omega(t, x)} dy dz, \quad Q_{sl}(t, x) = A_{sl}(t, x) u(t, x)$$

$$u(t, x) = \frac{1}{A_{sl}(t, x)} \int_{\Omega(t, x)} U(t, x) dy dz$$



J.-F. Gerbeau, B. Perthame

Derivation of viscous Saint-Venant System for Laminar Shallow Water; Numerical Validation.
Discrete and Continuous Dynamical Systems, Ser. B, Vol. 1, Num. 1, 89–102, 2001.



F. Marche

Derivation of a new two-dimensional viscous shallow water model with varying topography, bottom friction and capillary effects.
European Journal of Mechanics B/Fluid, 26 (2007), 49–63.

DERIVATION OF THE FREE SURFACE MODEL

3D INCOMPRESSIBLE EULER EQUATIONS

$$\begin{aligned}\rho_0 \operatorname{div}(\mathbf{U}) &= 0 \\ \rho_0 (\partial_t \mathbf{U} + \mathbf{U} \cdot \nabla \mathbf{U}) + \nabla p &= \rho_0 F\end{aligned}$$

Method :

- 1 Write Euler equations in curvilinear coordinates.
- 2 Write equations in non-dimensional form using the small parameter $\epsilon = H/L$ and takes $\epsilon = 0$.
- 3 Section averaging $\overline{U^2} \approx \overline{U} \overline{U}$ and $\overline{UV} \approx \overline{U} \overline{V}$.
- 4 Introduce $A_{sl}(t, x)$: wet area, $Q_{sl}(t, x)$ discharge given by :

$$A_{sl}(t, x) = \int_{\Omega(t, x)} dydz, \quad Q_{sl}(t, x) = A_{sl}(t, x)u(t, x)$$

$$u(t, x) = \frac{1}{A_{sl}(t, x)} \int_{\Omega(t, x)} U(t, x) dydz$$


DERIVATION OF THE FREE SURFACE MODEL

3D INCOMPRESSIBLE EULER EQUATIONS

$$\begin{aligned}\rho_0 \operatorname{div}(\mathbf{U}) &= 0 \\ \rho_0 (\partial_t \mathbf{U} + \mathbf{U} \cdot \nabla \mathbf{U}) + \nabla p &= \rho_0 \mathbf{F}\end{aligned}$$

Method :

- 1 Write Euler equations in curvilinear coordinates.
- 2 Write equations in non-dimensional form using the small parameter $\epsilon = H/L$ and takes $\epsilon = 0$.
- 3 Section averaging $\overline{U^2} \approx \overline{U} \overline{U}$ and $\overline{UV} \approx \overline{U} \overline{V}$.
- 4 Introduce $A_{sl}(t, x)$: wet area, $Q_{sl}(t, x)$ discharge given by :



$$A_{sl}(t, x) = \int_{\Omega(t, x)} dydz, \quad Q_{sl}(t, x) = A_{sl}(t, x)u(t, x)$$

$$u(t, x) = \frac{1}{A_{sl}(t, x)} \int_{\Omega(t, x)} U(t, x) dydz$$

THE FREE SURFACE MODEL

$$\left\{ \begin{array}{l} \partial_t A_{sl} + \partial_x Q_{sl} = 0, \\ \partial_t Q_{sl} + \partial_x \left(\frac{Q_{sl}^2}{A_{sl}} + p_{sl}(x, A_{sl}) \right) = -g A_{sl} \frac{dZ}{dx} + Pr_{sl}(x, A_{sl}) - G(x, A_{sl}) \end{array} \right.$$

with

$$p_{sl} = g I_1(x, A_{sl}) \cos \theta \quad : \text{hydrostatic pressure law}$$

$$Pr_{sl} = g I_2(x, A_{sl}) \cos \theta \quad : \text{pressure source term}$$

$$G = g A_{sl} \bar{z} \frac{d}{dx} \cos \theta \quad : \text{curvature source term}$$

THE FREE SURFACE MODEL

$$\left\{ \begin{array}{l} \partial_t A_{sl} + \partial_x Q_{sl} = 0, \\ \partial_t Q_{sl} + \partial_x \left(\frac{Q_{sl}^2}{A_{sl}} + p_{sl}(x, A_{sl}) \right) = -g A_{sl} \frac{dZ}{dx} + Pr_{sl}(x, A_{sl}) - G(x, A_{sl}) \\ \quad - \underbrace{g K(x, A_{sl}) \frac{Q_{sl} |Q_{sl}|}{A_{sl}}}_{\text{friction added after the derivation}} \end{array} \right.$$

with

$$p_{sl} = g I_1(x, A_{sl}) \cos \theta \quad : \text{hydrostatic pressure law}$$

$$Pr_{sl} = g I_2(x, A_{sl}) \cos \theta \quad : \text{pressure source term}$$

$$G = g A_{sl} \bar{z} \frac{d}{dx} \cos \theta \quad : \text{curvature source term}$$

$$K = \frac{1}{K_s^2 R_h (A_{sl})^{4/3}} \quad : \text{Manning-Strickler law}$$

DERIVATION OF THE PRESSURIZED MODEL

3D ISENTROPIC COMPRESSIBLE EQUATIONS

$$\partial_t \rho + \operatorname{div}(\rho \mathbf{U}) = 0$$

$$\partial_t(\rho \mathbf{U}) + \operatorname{div}(\rho \mathbf{U} \otimes \mathbf{U}) + \nabla p = \rho \mathbf{F}$$

with

$$p = p_a + \frac{\rho - \rho_0}{c^2} \text{ with } c \text{ sound speed}$$

Method :

- 1 Write Euler equations in curvilinear coordinates.
- 2 Write equations in non-dimensional form using the small parameter $\epsilon = H/L$ and takes $\epsilon = 0$.
- 3 Section averaging $\overline{\rho U} \approx \bar{\rho} \bar{U}$ and $\overline{\rho U^2} \approx \bar{\rho} \bar{U} \bar{U}$.
- 4 Introduce $A_{ch}(t, x)$: equivalent wet area, $Q_{ch}(t, x)$ discharge given by :

$$A_{ch}(t, x) = \frac{\bar{\rho}}{\rho_0} S(x), \quad Q_{ch}(t, x) = A_{ch}(t, x) u(t, x)$$

$$u(t, x) = \frac{1}{S(x)} \int_{\Omega(x)} U(t, x) \, dy dz$$

DERIVATION OF THE PRESSURIZED MODEL

3D ISENTROPIC COMPRESSIBLE EQUATIONS

$$\partial_t \rho + \operatorname{div}(\rho \mathbf{U}) = 0$$

$$\partial_t(\rho \mathbf{U}) + \operatorname{div}(\rho \mathbf{U} \otimes \mathbf{U}) + \nabla p = \rho \mathbf{F}$$

with

$$p = p_a + \frac{\rho - \rho_0}{c^2} \text{ with } c \text{ sound speed}$$

Method :

- 1 Write Euler equations in curvilinear coordinates.
- 2 Write equations in non-dimensional form using the small parameter $\epsilon = H/L$ and takes $\epsilon = 0$.
- 3 Section averaging $\overline{\rho U} \approx \bar{\rho} \bar{U}$ and $\overline{\rho U^2} \approx \bar{\rho} \bar{U} \bar{U}$.
- 4 Introduce $A_{ch}(t, x)$: equivalent wet area, $Q_{ch}(t, x)$ discharge given by :

$$A_{ch}(t, x) = \frac{\bar{\rho}}{\rho_0} S(x), \quad Q_{ch}(t, x) = A_{ch}(t, x) u(t, x)$$

$$u(t, x) = \frac{1}{S(x)} \int_{\Omega(x)} U(t, x) \, dy dz$$

DERIVATION OF THE PRESSURIZED MODEL

3D ISENTROPIC COMPRESSIBLE EQUATIONS

$$\partial_t \rho + \operatorname{div}(\rho \mathbf{U}) = 0$$

$$\partial_t(\rho \mathbf{U}) + \operatorname{div}(\rho \mathbf{U} \otimes \mathbf{U}) + \nabla p = \rho \mathbf{F}$$

with

$$p = p_a + \frac{\rho - \rho_0}{c^2} \text{ with } c \text{ sound speed}$$

Method :

- 1 Write Euler equations in curvilinear coordinates.
- 2 Write equations in non-dimensional form using the small parameter $\epsilon = H/L$ and takes $\epsilon = 0$.
- 3 Section averaging $\overline{\rho U} \approx \bar{\rho} \bar{U}$ and $\overline{\rho U^2} \approx \bar{\rho} \bar{U} \bar{U}$.
- 4 Introduce $A_{ch}(t, x)$: equivalent wet area, $Q_{ch}(t, x)$ discharge given by :

$$A_{ch}(t, x) = \frac{\bar{\rho}}{\rho_0} S(x), \quad Q_{ch}(t, x) = A_{ch}(t, x) u(t, x)$$

$$u(t, x) = \frac{1}{S(x)} \int_{\Omega(x)} U(t, x) \, dy dz$$

DERIVATION OF THE PRESSURIZED MODEL

3D ISENTROPIC COMPRESSIBLE EQUATIONS

$$\partial_t \rho + \operatorname{div}(\rho \mathbf{U}) = 0$$


$$\partial_t(\rho \mathbf{U}) + \operatorname{div}(\rho \mathbf{U} \otimes \mathbf{U}) + \nabla p = \rho \mathbf{F}$$

with

$$p = p_a + \frac{\rho - \rho_0}{c^2} \text{ with } c \text{ sound speed}$$

Method :

- 1 Write Euler equations in curvilinear coordinates.
- 2 Write equations in non-dimensional form using the small parameter $\epsilon = H/L$ and takes $\epsilon = 0$.
- 3 Section averaging $\overline{\rho U} \approx \bar{\rho} \bar{U}$ and $\overline{\rho U^2} \approx \bar{\rho} \bar{U} \bar{U}$.
- 4 Introduce $A_{ch}(t, x)$: equivalent wet area, $Q_{ch}(t, x)$ discharge given by :



$$A_{ch}(t, x) = \frac{\bar{\rho}}{\rho_0} S(x), \quad Q_{ch}(t, x) = A_{ch}(t, x) u(t, x)$$

$$u(t, x) = \frac{1}{S(x)} \int_{\Omega(x)} U(t, x) dy dz$$

THE PRESSURIZED MODEL

$$\left\{ \begin{array}{l} \partial_t A_{ch} + \partial_x Q_{ch} = 0, \\ \partial_t Q_{ch} + \partial_x \left(\frac{Q_{ch}^2}{A_{ch}} + p_{ch}(x, A_{ch}) \right) = -g A_{ch} \frac{dZ}{dx} + Pr_{ch}(x, A_{ch}) - G(x, A_{ch}) \end{array} \right.$$

with

$$p_{ch} = c^2(A_{ch} - S) \quad : \text{acoustic type pressure law}$$

$$Pr_{ch} = c^2 \left(\frac{A_{ch}}{S} - 1 \right) \frac{dS}{dx} \quad : \text{pressure source term}$$

$$G = g A_{ch} \bar{z} \frac{d}{dx} \cos \theta \quad : \text{curvature source term}$$

THE PRESSURIZED MODEL

$$\left\{ \begin{array}{l} \partial_t A_{ch} + \partial_x Q_{ch} = 0, \\ \partial_t Q_{ch} + \partial_x \left(\frac{Q_{ch}^2}{A_{ch}} + p_{ch}(x, A_{ch}) \right) = -g A_{ch} \frac{dZ}{dx} + Pr_{ch}(x, A_{ch}) - G(x, A_{ch}) \\ \quad - \underbrace{g K(x, S) \frac{Q_{ch} |Q_{ch}|}{A_{ch}}}_{\text{friction added after the derivation}} \end{array} \right.$$

with

$$p_{ch} = c^2 (A_{ch} - S) \quad : \text{acoustic type pressure law}$$

$$Pr_{ch} = c^2 \left(\frac{A_{ch}}{S} - 1 \right) \frac{dS}{dx} \quad : \text{pressure source term}$$

$$G = g A_{ch} \bar{z} \frac{d}{dx} \cos \theta \quad : \text{curvature source term}$$

$$K = \frac{1}{K_s^2 R_h(S)^{4/3}} \quad : \text{Manning-Strickler law}$$

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

THE PFS MODEL

MODELS ARE FORMALLY CLOSE ...


$$\left\{ \begin{array}{l} \partial_t A_{sl} + \partial_x Q_{sl} \\ \partial_t Q_{sl} + \partial_x \left(\frac{Q_{sl}^2}{A_{sl}} + p_{sl}(x, A_{sl}) \right) \end{array} \right. = \begin{array}{l} 0, \\ -g A_{sl} \frac{dZ}{dx} + Pr_{sl}(x, A_{sl}) \\ -G(x, A_{sl}) \\ -gK(x, A_{sl}) \frac{Q_{sl}|Q_{sl}|}{A_{sl}} \end{array}$$

$$\left\{ \begin{array}{l} \partial_t A_{ch} + \partial_x Q_{ch} \\ \partial_t Q_{ch} + \partial_x \left(\frac{Q_{ch}^2}{A_{ch}} + p_{ch}(x, A_{ch}) \right) \end{array} \right. = \begin{array}{l} 0, \\ -g A_{ch} \frac{dZ}{dx} + Pr_{ch}(x, A_{ch}) \\ -G(x, A_{ch}) \\ -gK(x, S) \frac{Q_{ch}|Q_{ch}|}{A_{ch}} \end{array}$$

THE PFS MODEL

MODELS ARE FORMALLY CLOSE ...

$$\left\{ \begin{array}{l} \partial_t A_{sl} + \partial_x Q_{sl} = 0, \\ \partial_t Q_{sl} + \partial_x \left(\frac{Q_{sl}^2}{A_{sl}} + p_{sl}(x, A_{sl}) \right) = -g A_{sl} \frac{dZ}{dx} + Pr_{sl}(x, A_{sl}) \\ \quad - G(x, A_{sl}) \\ \quad - gK(x, A_{sl}) \frac{Q_{sl}|Q_{sl}|}{A_{sl}} \end{array} \right.$$

$$\left\{ \begin{array}{l} \partial_t A_{ch} + \partial_x Q_{ch} = 0, \\ \partial_t Q_{ch} + \partial_x \left(\frac{Q_{ch}^2}{A_{ch}} + p_{ch}(x, A_{ch}) \right) = -g A_{ch} \frac{dZ}{dx} + Pr_{ch}(x, A_{ch}) \\ \quad - G(x, A_{ch}) \\ \quad - gK(x, S) \frac{Q_{ch}|Q_{ch}|}{A_{ch}} \end{array} \right.$$


Continuity criterion

THE PFS MODEL

MODELS ARE FORMALLY CLOSE ...



$$\left\{ \begin{array}{l} \partial_t A_{sl} + \partial_x Q_{sl} = 0, \\ \partial_t Q_{sl} + \partial_x \left(\frac{Q_{sl}^2}{A_{sl}} + p_{sl}(x, A_{sl}) \right) = -g \underbrace{A_{sl}}_{\uparrow} \frac{dZ}{dx} + Pr_{sl}(x, A_{sl}) \\ \quad - G(x, \underbrace{A_{sl}}_{\downarrow}) \\ \quad - g \underbrace{K(x, A_{sl})}_{\downarrow} \frac{Q_{sl}|Q_{sl}|}{A_{sl}} \end{array} \right.$$



$$\left\{ \begin{array}{l} \partial_t A_{ch} + \partial_x Q_{ch} = 0, \\ \partial_t Q_{ch} + \partial_x \left(\frac{Q_{ch}^2}{A_{ch}} + p_{ch}(x, A_{ch}) \right) = -g \underbrace{A_{ch}}_{\uparrow} \frac{dZ}{dx} + Pr_{ch}(x, A_{ch}) \\ \quad - G(x, \underbrace{A_{ch}}_{\downarrow}) \\ \quad - g \underbrace{K(x, S)}_{\downarrow} \frac{Q_{ch}|Q_{ch}|}{A_{ch}} \end{array} \right.$$

« mixed » condition

THE PFS MODEL

MODELS ARE FORMALLY CLOSE ...

$$\begin{cases} \partial_t A_{sl} + \partial_x Q_{sl} \\ \partial_t Q_{sl} + \partial_x \left(\frac{Q_{sl}^2}{A_{sl}} + p_{sl}(x, A_{sl}) \right) \end{cases} = \begin{cases} 0, \\ -g A_{sl} \frac{dZ}{dx} - Pr_{sl}(x, A_{sl}) \\ -G(x, A_{sl}) \\ -gK(x, A_{sl}) \frac{Q_{sl}|Q_{sl}|}{A_{sl}} \end{cases}$$



$$\begin{cases} \partial_t A_{ch} + \partial_x Q_{ch} \\ \partial_t Q_{ch} + \partial_x \left(\frac{Q_{ch}^2}{A_{ch}} + p_{ch}(x, A_{ch}) \right) \end{cases} = \begin{cases} 0, \\ -g A_{ch} \frac{dZ}{dx} - Pr_{ch}(x, A_{ch}) \\ -G(x, A_{ch}) \\ -gK(x, S) \frac{Q_{ch}|Q_{ch}|}{A_{ch}} \end{cases}$$



To be coupled

THE PFS MODEL

THE « MIXED » VARIABLE

We introduce a **state indicator**

$$E = \begin{cases} 1 & \text{if the flow is pressurized (CH),} \\ 0 & \text{if the flow is free surface (SL)} \end{cases}$$

THE PFS MODEL

THE « MIXED » VARIABLE

We introduce a **state indicator**

$$E = \begin{cases} 1 & \text{if the flow is pressurized (CH),} \\ 0 & \text{if the flow is free surface (SL)} \end{cases}$$

and the **physical section of water** **S** by :

$$\mathbf{S} = \mathbf{S}(A_{sl}, E) = \begin{cases} S & \text{if } E = 1, \\ A_{sl} & \text{if } E = 0. \end{cases}$$

THE PFS MODEL

THE « MIXED » VARIABLE

We introduce a **state indicator**

$$E = \begin{cases} 1 & \text{if the flow is pressurized (CH),} \\ 0 & \text{if the flow is free surface (SL)} \end{cases}$$

and the **physical section of water** **S** by :

$$\mathbf{S} = \mathbf{S}(A_{sl}, E) = \begin{cases} S & \text{if } E = 1, \\ A_{sl} & \text{if } E = 0. \end{cases}$$

We set

$$\begin{aligned} A &= \frac{\bar{\rho}}{\rho_0} \mathbf{S} = \begin{cases} \mathbf{S}(A_{sl}, 0) = A_{sl} & \text{if SL} \\ \frac{\bar{\rho}}{\rho_0} \mathbf{S}(A_{sl}, 1) = A_{ch} & \text{if CH} \end{cases} : \text{ the « mixed » variable} \\ Q &= Au : \text{ the discharge} \end{aligned}$$

THE PFS MODEL

THE « MIXED » VARIABLE

We introduce a **state indicator**

$$E = \begin{cases} 1 & \text{if the flow is pressurized (CH),} \\ 0 & \text{if the flow is free surface (SL)} \end{cases}$$

and the **physical section of water** **S** by :

$$\mathbf{S} = \mathbf{S}(A_{sl}, E) = \begin{cases} S & \text{if } E = 1, \\ A_{sl} & \text{if } E = 0. \end{cases}$$

We set

$$\begin{aligned} A &= \frac{\bar{\rho}}{\rho_0} \mathbf{S} = \begin{cases} \mathbf{S}(A_{sl}, 0) = A_{sl} & \text{if SL} \\ \frac{\bar{\rho}}{\rho_0} \mathbf{S}(A_{sl}, 1) = A_{ch} & \text{if CH} \end{cases} : \text{ the « mixed » variable} \\ Q &= Au : \text{ the discharge} \end{aligned}$$

Continuity of **S** at transition point

THE PFS MODEL

CONSTRUCTION OF THE « MIXED » PRESSURE

- Continuity of $\mathbf{S} \implies$ continuity of p at transition point



$$p(x, A, E) = c^2(A - \mathbf{S}) + gI_1(x, \mathbf{S}) \cos \theta$$

THE PFS MODEL

CONSTRUCTION OF THE « MIXED » PRESSURE

- Continuity of $\mathbf{S} \implies$ continuity of p at transition point



$$p(x, A, E) = c^2(A - \mathbf{S}) + gI_1(x, \mathbf{S}) \cos \theta$$

- Similar construction for the pressure source term :

$$Pr(x, A, E) = c^2 \left(\frac{A}{\mathbf{S}} - 1 \right) \frac{dS}{dx} + gI_2(x, \mathbf{S}) \cos \theta$$

THE PFS MODEL

$$\left\{ \begin{array}{l} \partial_t(A) + \partial_x(Q) \\ \partial_t(Q) + \partial_x \left(\frac{Q^2}{A} + p(x, A, E) \right) \\ \\ \\ \end{array} \right. \begin{array}{l} = 0 \\ = -g A \frac{d}{dx} Z(x) \\ + Pr(x, A, E) \\ - G(x, A, E) \\ - g K(x, \mathbf{s}) \frac{Q|Q|}{A} \end{array}$$



C. Bourdarias, M. Ersoy and S. Gerbi

A model for unsteady mixed flows in non uniform closed water pipes and a well-balanced finite volume scheme.

Int. J. On Finite Volumes, 6(2) :1–47, 2009.

THE PFS MODEL

MATHEMATICAL PROPERTIES

- The **PFS** system is **strictly hyperbolic** for $A(t, x) > 0$.
- For regular solutions, the mean speed $u = Q/A$ verifies

$$\partial_t u + \partial_x \left(\frac{u^2}{2} + c^2 \ln(A/S) + g \mathcal{H}(S) \cos \theta + g Z \right) = -g K(x, \mathbf{S}) u |u|$$

and **for** $u = 0$, we have :

$$c^2 \ln(A/\mathbf{S}) + g \mathcal{H}(\mathbf{S}) \cos \theta + g Z = cte$$

where $\mathcal{H}(\mathbf{S})$ is the physical water height.

- There exists a **mathematical entropy**

$$E(A, Q, S) = \frac{Q^2}{2A} + c^2 A \ln(A/\mathbf{S}) + c^2 S + g \bar{z}(x, \mathbf{S}) \cos \theta + g A Z$$

which satisfies

$$\partial_t E + \partial_x (E u + p(x, A, E) u) = -g A K(x, \mathbf{S}) u^2 |u| \leq 0$$

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)


- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES


FINITE VOLUME (VF) NUMERICAL SCHEME OF ORDER 1



PFS equations under vectorial form :

$$\partial_t \mathbf{U}(t, x) + \partial_x F(x, \mathbf{U}) = \mathcal{S}(t, x)$$

FINITE VOLUME (VF) NUMERICAL SCHEME OF ORDER 1




PFS equations under vectorial form :

$$\partial_t \mathbf{U}(t, x) + \partial_x F(x, \mathbf{U}) = \mathcal{S}(t, x)$$

with \mathbf{U}_i^n cte per mesh $\approx \frac{1}{\Delta x} \int_{m_i} \mathbf{U}(t_n, x) dx$ and $\mathcal{S}(t, x)$ constant per mesh,

FINITE VOLUME (VF) NUMERICAL SCHEME OF ORDER 1



PFS equations under vectorial form :

$$\partial_t \mathbf{U}(t, x) + \partial_x F(x, \mathbf{U}) = \mathcal{S}(t, x)$$

with \mathbf{U}_i^n cte per mesh $\approx \frac{1}{\Delta x} \int_{m_i} \mathbf{U}(t_n, x) dx$ and $\mathcal{S}(t, x)$ constant per mesh,


Cell-centered numerical scheme :

$$\mathbf{U}_i^{n+1} = \mathbf{U}_i^n - \frac{\Delta t^n}{\Delta x} (\mathcal{F}_{i+1/2} - \mathcal{F}_{i-1/2}) + \Delta t^n \mathcal{S}(\mathbf{U}_i^n)$$

where

$$\Delta t^n \mathcal{S}_i^n \approx \int_{t_n}^{t_{n+1}} \int_{m_i} \mathcal{S}(t, x) dx dt$$

FINITE VOLUME (VF) NUMERICAL SCHEME OF ORDER 1



PFS equations under vectorial form :

$$\partial_t \mathbf{U}(t, x) + \partial_x F(x, \mathbf{U}) = \mathcal{S}(t, x)$$

with $\mathbf{U}_i^n \stackrel{\text{cte per mesh}}{\approx} \frac{1}{\Delta x} \int_{m_i} \mathbf{U}(t_n, x) dx$ and $\mathcal{S}(t, x)$ constant per mesh,

Upwinded numerical scheme :

$$\mathbf{U}_i^{n+1} = \mathbf{U}_i^n - \frac{\Delta t^n}{\Delta x} \left(\tilde{\mathcal{F}}_{i+1/2} - \tilde{\mathcal{F}}_{i-1/2} \right)$$

\mathcal{F} and $\tilde{\mathcal{F}}$ are consistent.

CHOICE OF THE NUMERICAL FLUXES

Our goal : define $\mathcal{F}_{i+1/2}$ in order to preserve continuous properties of the PFS-model

Positivity of A ,
conservativity of A , discrete equilibrium, discrete entropy inequality

CHOICE OF THE NUMERICAL FLUXES

Our goal : define $\mathcal{F}_{i+1/2}$ in order to preserve continuous properties of the PFS-model

Positivity of A ,

conservativity of A , discrete equilibrium, discrete entropy inequality

CHOICE OF THE NUMERICAL FLUXES

Our goal : define $\mathcal{F}_{i+1/2}$ in order to preserve continuous properties of the PFS-model

Positivity of A ,

conservativity of A , discrete equilibrium, discrete entropy inequality

CHOICE OF THE NUMERICAL FLUXES

Our goal : define $\mathcal{F}_{i+1/2}$ in order to preserve continuous properties of the PFS-model

Positivity of A ,
conservativity of A , discrete equilibrium, discrete entropy inequality

Our choice

VFRoe solver[BEGVF]

Kinetic solver[BEG10]



C. Bourdarias, M. Ersoy and S. Gerbi.

A model for unsteady mixed flows in non uniform closed water pipes and a well-balanced finite volume scheme.
International Journal On Finite Volumes , Vol 6(2) 1–47, 2009.



C. Bourdarias, M. Ersoy and S. Gerbi.

A kinetic scheme for transient mixed flows in non uniform closed pipes : a global manner to upwind all the source terms.
J. Sci. Comp., pp 1-16, 10.1007/s10915-010-9456-0, 2011.

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK


- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

PHILOSOPHY

As in kinetic theory of gases,


Describe the *macroscopic behavior* from *particle motions*, here, assumed fictitious by introducing $\left\{ \begin{array}{l} \text{a } \chi \text{ density function and} \\ \text{a } \mathcal{M}(t, x, \xi; \chi) \text{ maxwellian function (or a Gibbs equilibrium)} \end{array} \right.$



PHILOSOPHY

As in kinetic theory of gases,

Describe the macroscopic behavior from particle motions, here, assumed fictitious
by introducing $\left\{ \begin{array}{l} \text{a } \chi \text{ density function and} \\ \text{a } \mathcal{M}(t, x, \xi; \chi) \text{ maxwellian function (or a Gibbs equilibrium)} \end{array} \right.$




i.e., transform the **nonlinear system** into a **kinetic transport equation** on \mathcal{M} .

PHILOSOPHY

As in kinetic theory of gases,

Describe the macroscopic behavior from particle motions, here, assumed fictitious
by introducing $\left\{ \begin{array}{l} \text{a } \chi \text{ density function and} \\ \text{a } \mathcal{M}(t, x, \xi; \chi) \text{ maxwellian function (or a Gibbs equilibrium)} \end{array} \right.$



i.e., transform the nonlinear system into a kinetic transport equation on \mathcal{M} .

Thus, to be able to define the numerical *macroscopic fluxes* from **the** microscopic one.

...Faire d'une pierre deux coups...

PRINCIPLE

DENSITY FUNCTION

We introduce

$$\chi(\omega) = \chi(-\omega) \geq 0, \quad \int_{\mathbb{R}} \chi(\omega) d\omega = 1, \quad \int_{\mathbb{R}} \omega^2 \chi(\omega) d\omega = 1,$$

PRINCIPLE

GIBBS EQUILIBRIUM OR MAXWELLIAN

We introduce

$$\chi(\omega) = \chi(-\omega) \geq 0, \quad \int_{\mathbb{R}} \chi(\omega) d\omega = 1, \quad \int_{\mathbb{R}} \omega^2 \chi(\omega) d\omega = 1,$$

then we define the **Gibbs equilibrium** by

$$\mathcal{M}(t, x, \xi) = \frac{A(t, x)}{b(t, x)} \chi\left(\frac{\xi - u(t, x)}{b(t, x)}\right)$$

with

$$b(t, x) = \sqrt{\frac{p(t, x)}{A(t, x)}}$$

PRINCIPLE

Since

$$\chi(\omega) = \chi(-\omega) \geq 0, \quad \int_{\mathbb{R}} \chi(\omega) d\omega = 1, \quad \int_{\mathbb{R}} \omega^2 \chi(\omega) d\omega = 1,$$

and

$$\mathcal{M}(t, x, \xi) = \frac{A(t, x)}{b(t, x)} \chi\left(\frac{\xi - u(t, x)}{b(t, x)}\right)$$

then

MICRO-MACROSCOPIC RELATIONS

$$\begin{aligned} A &= \int_{\mathbb{R}} \mathcal{M}(t, x, \xi) d\xi \\ Q &= \int_{\mathbb{R}} \xi \mathcal{M}(t, x, \xi) d\xi \\ \frac{Q^2}{A} + \underbrace{A b^2}_p &= \int_{\mathbb{R}} \xi^2 \mathcal{M}(t, x, \xi) d\xi \end{aligned}$$

PRINCIPLE [P02]

THE KINETIC FORMULATION

(A, Q) is solution of the PFS system if and only if \mathcal{M} satisfy the transport equation :

$$\partial_t \mathcal{M} + \xi \cdot \partial_x \mathcal{M} - g \Phi \partial_\xi \mathcal{M} = \mathcal{K}(t, x, \xi)$$

where $\mathcal{K}(t, x, \xi)$ is a collision kernel satisfying a.e. (t, x)

$$\int_{\mathbb{R}} \mathcal{K} d\xi = 0, \quad \int_{\mathbb{R}} \xi \mathcal{K} d\xi = 0$$

and Φ are the source terms.



B. Perthame.

Kinetic formulation of conservation laws.

Oxford University Press.

Oxford Lecture Series in Mathematics and its Applications, Vol 21, 2002.

PRINCIPE

THE KINETIC FORMULATION

(A, Q) is solution of the PFS system if and only if \mathcal{M} satisfy the transport equation :

$$\partial_t \mathcal{M} + \xi \cdot \partial_x \mathcal{M} - g \Phi \partial_\xi \mathcal{M} = \mathcal{K}(t, x, \xi)$$

where $\mathcal{K}(t, x, \xi)$ is a collision kernel satisfying a.e. (t, x)

$$\int_{\mathbb{R}} \mathcal{K} d\xi = 0, \quad \int_{\mathbb{R}} \xi \mathcal{K} d\xi = 0$$

and Φ are the source terms.

General form of the source terms :

$$\Phi = \overbrace{\frac{d}{dx} Z}^{\text{conservative}} + \overbrace{\mathbf{B} \cdot \frac{d}{dx} \mathbf{W}}^{\text{non conservative}} + \overbrace{K \frac{Q|Q|}{A^2}}^{\text{friction}}$$

with $\mathbf{W} = (Z, S, \cos \theta)$

DISCRETIZATION OF SOURCE TERMS

- Recalling that A, Q and $Z, S, \cos \theta$ constant per mesh
- forgetting the friction : « splitting »...

DISCRETIZATION OF SOURCE TERMS

- Recalling that A, Q and $Z, S, \cos \theta$ constant per mesh
- forgetting the friction : « splitting »...

Then $\forall (t, x) \in [t_n, t_{n+1}[\times \overset{\circ}{m}_i$

$$\Phi(t, x) = 0$$

since

$$\Phi = \frac{d}{dx} Z + \mathbf{B} \cdot \frac{d}{dx} \mathbf{W}$$

SIMPLIFICATION OF THE TRANSPORT EQUATION

- Recalling that A, Q and $Z, S, \cos \theta$ constant per mesh
- forgetting the friction : « splitting »...

Then $\forall (t, x) \in [t_n, t_{n+1}[\times \overset{\circ}{m}_i$

$$\Phi(t, x) = 0$$

since

$$\Phi = \frac{d}{dx} Z + \mathbf{B} \cdot \frac{d}{dx} \mathbf{W}$$



$$\partial_t \mathcal{M} + \xi \cdot \partial_x \mathcal{M} = \mathcal{K}(t, x, \xi)$$

SIMPLIFICATION OF THE TRANSPORT EQUATION

- Recalling that A, Q and $Z, S, \cos \theta$ constant per mesh
- forgetting the friction : « splitting »...

Then $\forall (t, x) \in [t_n, t_{n+1}[\times \overset{\circ}{m}_i$

$$\Phi(t, x) = 0$$

since

$$\Phi = \frac{d}{dx} Z + \mathbf{B} \cdot \frac{d}{dx} \mathbf{W}$$

\Rightarrow

$$\begin{cases} \partial_t f + \xi \cdot \partial_x f &= 0 \\ f(t_n, x, \xi) &= \mathcal{M}(t_n, x, \xi) \stackrel{\text{def}}{=} \frac{A(t_n, x, \xi)}{b(t_n, x, \xi)} \chi \left(\frac{\xi - u(t_n, x, \xi)}{b(t_n, x, \xi)} \right) \end{cases}$$

by neglecting the collision kernel.

DISCRETIZATION OF SOURCE TERMS

On $[t_n, t_{n+1}[\times m_i$, we have :

$$\begin{cases} \partial_t f + \xi \cdot \partial_x f &= 0 \\ f(t_n, x, \xi) &= \mathcal{M}_i^n(\xi) \end{cases}$$

DISCRETIZATION OF SOURCE TERMS

On $[t_n, t_{n+1}[\times m_i$, we have :

$$\begin{cases} \partial_t f + \xi \cdot \partial_x f &= 0 \\ f(t_n, x, \xi) &= \mathcal{M}_i^n(\xi) \end{cases}$$

i.e.

$$f_i^{n+1}(\xi) = \mathcal{M}_i^n(\xi) + \xi \frac{\Delta t^n}{\Delta x} \left(\mathcal{M}_{i+\frac{1}{2}}^-(\xi) - \mathcal{M}_{i-\frac{1}{2}}^+(\xi) \right)$$

DISCRETIZATION OF SOURCE TERMS

On $[t_n, t_{n+1}[\times m_i$, we have :

$$\begin{cases} \partial_t f + \xi \cdot \partial_x f &= 0 \\ f(t_n, x, \xi) &= \mathcal{M}_i^n(\xi) \end{cases}$$

i.e.

$$f_i^{n+1}(\xi) = \mathcal{M}_i^n(\xi) + \xi \frac{\Delta t^n}{\Delta x} \left(\mathcal{M}_{i+\frac{1}{2}}^-(\xi) - \mathcal{M}_{i-\frac{1}{2}}^+(\xi) \right)$$

where

$$\mathbf{u}_i^{n+1} = \begin{pmatrix} A_i^{n+1} \\ Q_i^{n+1} \end{pmatrix} \stackrel{\text{def}}{=} \int_{\mathbb{R}} \begin{pmatrix} 1 \\ \xi \end{pmatrix} f_i^{n+1}(\xi) d\xi$$

DISCRETIZATION OF SOURCE TERMS

On $[t_n, t_{n+1}[\times m_i$, we have :

$$\begin{cases} \partial_t f + \xi \cdot \partial_x f &= 0 \\ f(t_n, x, \xi) &= \mathcal{M}_i^n(\xi) \end{cases}$$

i.e.

$$f_i^{n+1}(\xi) = \mathcal{M}_i^n(\xi) + \xi \frac{\Delta t^n}{\Delta x} \left(\mathcal{M}_{i+\frac{1}{2}}^-(\xi) - \mathcal{M}_{i-\frac{1}{2}}^+(\xi) \right)$$

or

$$\mathbf{u}_i^{n+1} = \mathbf{u}_i^n - \frac{\Delta t^n}{\Delta x} \left(\tilde{\mathcal{F}}_{i+1/2}^- - \tilde{\mathcal{F}}_{i-1/2}^+ \right)$$


with

$$\tilde{\mathcal{F}}_{i\pm\frac{1}{2}}^\pm = \int_{\mathbb{R}} \xi \begin{pmatrix} 1 \\ \xi \end{pmatrix} \mathcal{M}_{i\pm\frac{1}{2}}^\pm(\xi) d\xi.$$

THE MICROSCOPIC FLUXES

INTERPRETATION : POTENTIAL BAREER


$$\mathcal{M}_{i+1/2}^{-}(\xi) = \overbrace{\mathbb{1}_{\{\xi > 0\}} \mathcal{M}_i^n(\xi)}^{\text{positive transmission}} + \underbrace{\mathbb{1}_{\{\xi < 0, \xi^2 - 2g\Delta\Phi_{i+1/2}^n > 0\}} \mathcal{M}_{i+1}^n \left(-\sqrt{\xi^2 - 2g\Delta\Phi_{i+1/2}^n} \right)}_{\text{negative transmission}}$$



THE MICROSCOPIC FLUXES

INTERPRETATION : POTENTIAL BAREER


$$\mathcal{M}_{i+1/2}^{-}(\xi) = \overbrace{\mathbb{1}_{\{\xi>0\}}\mathcal{M}_i^n(\xi)}^{\text{positive transmission}} + \overbrace{\mathbb{1}_{\{\xi<0, \xi^2-2g\Delta\Phi_{i+1/2}^n<0\}}\mathcal{M}_i^n(-\xi)}^{\text{reflection}} \\ + \underbrace{\mathbb{1}_{\{\xi<0, \xi^2-2g\Delta\Phi_{i+1/2}^n>0\}}\mathcal{M}_{i+1}^n\left(-\sqrt{\xi^2-2g\Delta\Phi_{i+1/2}^n}\right)}_{\text{negative transmission}}$$



THE MICROSCOPIC FLUXES

INTERPRETATION : POTENTIAL BAREER

$$\mathcal{M}_{i+1/2}^{-}(\xi) = \overbrace{\mathbb{1}_{\{\xi>0\}}\mathcal{M}_i^n(\xi)}^{\text{positive transmission}} + \overbrace{\mathbb{1}_{\{\xi<0, \xi^2-2g\Delta\Phi_{i+1/2}^n<0\}}\mathcal{M}_i^n(-\xi)}^{\text{reflection}} \\ + \underbrace{\mathbb{1}_{\{\xi<0, \xi^2-2g\Delta\Phi_{i+1/2}^n>0\}}\mathcal{M}_{i+1}^n\left(-\sqrt{\xi^2-2g\Delta\Phi_{i+1/2}^n}\right)}_{\text{negative transmission}}$$




$\Delta\Phi_{i+1/2}^n$ may be interpreted as a time-dependent slope !

THE MICROSCOPIC FLUXES

INTERPRETATION : DYNAMIC SLOPE \implies UPWINDING OF THE FRICTION

$$\mathcal{M}_{i+1/2}^-(\xi) = \overbrace{\mathbb{1}_{\{\xi>0\}}\mathcal{M}_i^n(\xi)}^{\text{positive transmission}} + \overbrace{\mathbb{1}_{\{\xi<0, \xi^2-2g\Delta\Phi_{i+1/2}^n<0\}}\mathcal{M}_i^n(-\xi)}^{\text{reflection}} \\ + \underbrace{\mathbb{1}_{\{\xi<0, \xi^2-2g\Delta\Phi_{i+1/2}^n>0\}}\mathcal{M}_{i+1}^n\left(-\sqrt{\xi^2-2g\Delta\Phi_{i+1/2}^n}\right)}_{\text{negative transmission}}$$



$\Delta\Phi_{i+1/2}^n$ may be interpreted as a time-dependent slope !

... we reintegrate the friction ...

UPWINDING OF THE SOURCE TERMS : $\Delta\Phi_{i+1/2}$

- conservative $\partial_x \mathbf{W}$:

$$\mathbf{W}_{i+1} - \mathbf{W}_i$$

- non-conservative $\mathbf{B}\partial_x \mathbf{W}$:

$$\overline{\mathbf{B}}(\mathbf{W}_{i+1} - \mathbf{W}_i)$$

where

$$\overline{\mathbf{B}} = \int_0^1 \mathbf{B}(s, \phi(s, \mathbf{W}_i, \mathbf{W}_{i+1})) ds$$

for the « straight lines paths », i.e.

$$\phi(s, \mathbf{W}_i, \mathbf{W}_{i+1}) = s\mathbf{W}_{i+1} + (1-s)\mathbf{W}_i, s \in [0, 1]$$



G. Dal Maso, P. G. Lefloch and F. Murat.

Definition and weak stability of nonconservative products.
J. Math. Pures Appl. , Vol 74(6) 483–548, 1995.

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- **The χ function and well balanced scheme**
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

$\chi = ???$ IN PRACTICE $???$

Let us recall that we have to define a χ function such that :

$$\chi(\omega) = \chi(-\omega) \geq 0, \quad \int_{\mathbb{R}} \chi(\omega) d\omega = 1, \quad \int_{\mathbb{R}} \omega^2 \chi(\omega) d\omega = 1,$$

and $\mathcal{M} = \frac{A}{b} \chi\left(\frac{\xi - u}{b}\right)$ satisfies the equation :

$$\partial_t \mathcal{M} + \xi \cdot \partial_x \mathcal{M} - g \Phi \partial_\xi \mathcal{M} = 0$$

and

$\chi \longrightarrow$ definition of the macroscopic fluxes.

PROPERTIES RELATED TO χ

We always have

- Conservativity of A holds for every χ .
- Positivity of A holds for every χ but for numerical purpose iff $\text{supp}\chi$ is compact to get a CFL condition.

PROPERTIES RELATED TO χ

We always have

- Conservativity of A holds for every χ .
- Positivity of A holds for every χ but for numerical purpose iff $\text{supp}\chi$ is compact to get a CFL condition.

while

- discrete equilibrium,
- discrete entropy inequalities

strongly depend on the choice of the χ function.

PROPERTIES RELATED TO χ

We always have

- Conservativity of A holds for every χ .
- Positivity of A holds for every χ but for numerical purpose iff $\text{supp}\chi$ is compact to get a CFL condition.

while

- discrete equilibrium,
- discrete entropy inequalities

strongly depend on the choice of the χ function.

In the following, we only focus on discrete equilibrium.

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

STRATEGY

Even if the **pipe is circular with uniform cross-sections**, for instance for the free surface flows, the following procedure **fails** for complex source terms :

Following [PS01], choose χ such that $\mathcal{M}(t, x, \xi; \chi)$ is the steady state solution at rest, $u = 0$:

$$\xi \cdot \partial_x \mathcal{M} - g \Phi \partial_\xi \mathcal{M} = 0.$$

provides

$$\frac{3 T I_1 - A^2}{2 I_1} w \chi(w) + \left\{ \frac{A^2}{I_1} - w^2 \frac{A^2 - I_1 T}{2 I_1} \right\} \chi'(w) = 0 \text{ where } w = \frac{\xi}{b}.$$



B. Perthame and C. Simeoni

A kinetic scheme for the Saint-Venant system with a source term.
Calcolo, 38(4) :201–231, 2001.

STRATEGY

Even if the **pipe is circular with uniform cross-sections**, for instance for the free surface flows, the following procedure **fails** for complex source terms :

Following [PS01], choose χ such that $\mathcal{M}(t, x, \xi; \chi)$ is the steady state solution at rest, $u = 0$:

$$\xi \cdot \partial_x \mathcal{M} - g \Phi \partial_\xi \mathcal{M} = 0.$$

provides

$$\underbrace{\frac{3 T I_1 - A^2}{2 I_1}}_{\alpha} w \chi(w) + \left\{ \underbrace{\frac{A^2}{I_1}}_{\beta} - w^2 \underbrace{\frac{A^2 - I_1 T}{2 I_1}}_{\gamma} \right\} \chi'(w) = 0.$$

Then, this equation is solvable as an ODE iff the coefficients (α, β, γ) are constants.



B. Perthame and C. Simeoni

A kinetic scheme for the Saint-Venant system with a source term.
Calcolo, 38(4) :201–231, 2001.

STRATEGY

Even if the **pipe is circular with uniform cross-sections**, for instance for the free surface flows, the following procedure **fails** for complex source terms :

Following [PS01], choose χ such that $\mathcal{M}(t, x, \xi; \chi)$ is the steady state solution at rest, $u = 0$:

$$\xi \cdot \partial_x \mathcal{M} - g \Phi \partial_\xi \mathcal{M} = 0.$$

provides

$$\underbrace{\frac{3 T I_1 - A^2}{2 I_1}}_{\alpha} w \chi(w) + \left\{ \underbrace{\frac{A^2}{I_1}}_{\beta} - w^2 \underbrace{\frac{A^2 - I_1 T}{2 I_1}}_{\gamma} \right\} \chi'(w) = 0.$$

Then, this equation is solvable as an ODE iff the coefficients (α, β, γ) are constants.

For a rectangular pipe with uniform sections, we have $(\alpha, \beta, \gamma) = \left(\frac{T}{2}, 2T, \frac{T}{2} \right)$ with $T = cst$ the base of the pipe.



B. Perthame and C. Simeoni

A kinetic scheme for the Saint-Venant system with a source term.
Calcolo, 38(4) :201–231, 2001.

IN THESE SETTINGS

With $(\alpha, \beta, \gamma) = \left(\frac{T}{2}, 2T, \frac{T}{2}\right)$ and

THEOREM

we get $\chi(w) = \frac{1}{\pi} \left(1 - \frac{w^2}{4}\right)_+^{1/2}$ and the numerical scheme satisfies the following properties :

- Positivity of A (under a CFL condition),
- Conservativity of A ,
- Discrete equilibrium,
- Discrete entropy inequalities.

- This results holds only for conservative terms $\partial_x Z(x)$.
- A similar result for pressurized flows, unusable in practice (see [PhDErsoy Chap. 2]).



M. Ersoy

Modeling, mathematical and numerical analysis of various compressible or incompressible flows in thin layer [Modélisation, analyse mathématique et numérique de divers écoulements compressibles ou incompressibles en couche mince].

Université de Savoie, Chambéry, September 10, 2010.

IF (α, β, γ) ARE NOT CONSTANTS ...

Then, the equation to solve is :

$$\xi \cdot \partial_x \mathcal{M} - g \Phi \partial_\xi \mathcal{M} = 0.$$

Complicate to solve \longrightarrow find an easy way to maintain, at least, discrete steady states.

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

CORRECTION OF THE MACROSCOPIC FLUXES

The steady state is **perfectly maintained** iff

$$\widetilde{\mathcal{F}}_{i+1/2}^{-}(\mathbf{U}_i, \mathbf{U}_{i+1}, \mathbf{Z}_i, \mathbf{Z}_{i+1}) - \widetilde{\mathcal{F}}_{i-1/2}^{+}(\mathbf{U}_{i-1}, \mathbf{U}_i, \mathbf{Z}_{i-1}, \mathbf{Z}_i) = 0$$

with $\mathbf{U} = (A, Q)$, \mathbf{Z} = "source terms"

Notations : $F_{i\pm 1/2}$ the numerical flux of the homogeneous system, $\widetilde{F_{i\pm 1/2}}$ the numerical flux with source term and F the flux of the PFS-model.

CORRECTION OF THE MACROSCOPIC FLUXES

The steady state is perfectly maintained iff

$$\widetilde{\mathcal{F}}_{i+1/2}^{-}(\mathbf{U}_i, \mathbf{U}_{i+1}, \mathbf{Z}_i, \mathbf{Z}_{i+1}) - \widetilde{\mathcal{F}}_{i-1/2}^{+}(\mathbf{U}_{i-1}, \mathbf{U}_i, \mathbf{Z}_{i-1}, \mathbf{Z}_i) = 0$$

with $\mathbf{U} = (A, Q)$, \mathbf{Z} = "source terms"

Let us recall that without sources, whenever the numerical flux is consistent, i.e.

$$\forall \mathbf{U} = (A, Q) \in \mathbb{R}^2, F_{i\pm 1/2}(\mathbf{U}, \mathbf{U}) = F(\mathbf{U}),$$

we automatically have, whenever steady states occurs :

$$F_{i+1/2}^{-}(\mathbf{U}_i, \mathbf{U}_{i+1}) - F_{i-1/2}^{+}(\mathbf{U}_{i-1}, \mathbf{U}_i) = 0,$$

i.e.,

$$\mathbf{U}_i^{n+1} = \mathbf{U}_i^n.$$

Notations : $F_{i\pm 1/2}$ the numerical flux of the homogeneous system, $\widetilde{F_{i\pm 1/2}}$ the numerical flux with source term and F the flux of the PFS-model.

CORRECTION OF THE MACROSCOPIC FLUXES

The steady state is perfectly maintained iff

$$\tilde{\mathcal{F}}_{i+1/2}^{-}(\mathbf{U}_i, \mathbf{U}_{i+1}, \mathbf{Z}_i, \mathbf{Z}_{i+1}) - \tilde{\mathcal{F}}_{i-1/2}^{+}(\mathbf{U}_{i-1}, \mathbf{U}_i, \mathbf{Z}_{i-1}, \mathbf{Z}_i) = 0$$

with $\mathbf{U} = (A, Q)$, \mathbf{Z} = "source terms"

Let us recall that without sources, whenever the numerical flux is consistent, i.e.

$$\forall \mathbf{U} = (A, Q) \in \mathbb{R}^2, F_{i\pm 1/2}(\mathbf{U}, \mathbf{U}) = F(\mathbf{U}),$$

we automatically have, whenever steady states occurs :

$$F_{i+1/2}^{-}(\mathbf{U}_i, \mathbf{U}_{i+1}) - F_{i-1/2}^{+}(\mathbf{U}_{i-1}, \mathbf{U}_i) = 0,$$

i.e.,

$$\mathbf{U}_i^{n+1} = \mathbf{U}_i^n.$$

Correction of the numerical flux \rightarrow toward a **well balanced scheme**

Notations : $F_{i\pm 1/2}$ the numerical flux of the homogeneous system, $\widetilde{F_{i\pm 1/2}}$ the numerical flux with source term and F the flux of the PFS-model.

DEFINITION OF THE NEW FLUXES : M-SCHEME

IDEAS : replace

- dynamic quantities \mathbf{U}_{i-1} and \mathbf{U}_{i+1} by stationary profiles \mathbf{U}_{i-1}^+ and \mathbf{U}_{i+1}^-
- sources terms \mathbf{Z}_{i-1} and \mathbf{Z}_{i+1} by stationary profiles \mathbf{Z}_{i-1}^+ and \mathbf{Z}_{i+1}^-

DEFINITION OF THE NEW FLUXES : M-SCHEME

IDEAS : replace

- dynamic quantities \mathbf{U}_{i-1} and \mathbf{U}_{i+1} by stationary profiles \mathbf{U}_{i-1}^+ and \mathbf{U}_{i+1}^-
- sources terms \mathbf{Z}_{i-1} and \mathbf{Z}_{i+1} by stationary profiles \mathbf{Z}_{i-1}^+ and \mathbf{Z}_{i+1}^-

With A_{i+1}^- and A_{i-1}^+ computed from the steady states :

$$\forall i, \begin{cases} D(A_{i+1}^-, Q_{i+1}, \mathbf{Z}_i) &= D(\mathbf{U}_{i+1}, \mathbf{Z}_{i+1}) \\ D(A_{i-1}^+, Q_{i-1}, \mathbf{Z}_i) &= D(\mathbf{U}_{i-1}, \mathbf{Z}_{i-1}) \end{cases}$$

$$\text{where } D(\mathbf{U}, \mathbf{Z}) = \frac{Q^2}{2A} + \begin{cases} g\mathcal{H}(A) \cos \theta + gZ & \text{if } E = 0, \\ c^2 \ln \left(\frac{A}{S} \right) + g\mathcal{H}(S) \cos \theta + gZ & \text{if } E = 1. \end{cases}$$

And $(\mathbf{Z}_{i+1}^-, \mathbf{Z}_{i-1}^+)$ are defined as follows :

$$\mathbf{Z}_{i+1}^- = \begin{cases} \mathbf{Z}_i & \text{if } A_{i+1}^- = A_i \\ \mathbf{Z}_{i+1} & \text{if } A_{i+1}^- \neq A_i \end{cases}$$

$$\mathbf{Z}_{i-1}^+ = \begin{cases} \mathbf{Z}_i & \text{if } A_{i-1}^+ = A_i \\ \mathbf{Z}_{i-1} & \text{if } A_{i-1}^+ \neq A_i \end{cases}$$

DEFINITION OF THE NEW FLUXES : M-SCHEME

IDEAS : replace

- dynamic quantities \mathbf{U}_{i-1} and \mathbf{U}_{i+1} by stationary profiles \mathbf{U}_{i-1}^+ and \mathbf{U}_{i+1}^-
- sources terms \mathbf{Z}_{i-1} and \mathbf{Z}_{i+1} by stationary profiles \mathbf{Z}_{i-1}^+ and \mathbf{Z}_{i+1}^-

Let us now consider

$$\mathbf{U}_i^{n+1} = \mathbf{U}_i^n + \frac{\Delta t^n}{\Delta x} \left(\mathbf{F}_{i+\frac{1}{2}}^-(\mathbf{U}_i^n, A_{i+1}^-, Q_{i+1}^n, \mathbf{Z}_i, \mathbf{Z}_{i+1}^-) - \mathbf{F}_{i-\frac{1}{2}}^+(A_{i-1}^+, Q_{i-1}^n, \mathbf{U}_i^n, \mathbf{Z}_{i-1}^+, \mathbf{Z}_i) \right)$$

DEFINITION OF THE NEW FLUXES : M-SCHEME

IDEAS : replace


- dynamic quantities \mathbf{U}_{i-1} and \mathbf{U}_{i+1} by stationary profiles \mathbf{U}_{i-1}^+ and \mathbf{U}_{i+1}^-
- sources terms \mathbf{Z}_{i-1} and \mathbf{Z}_{i+1} by stationary profiles \mathbf{Z}_{i-1}^+ and \mathbf{Z}_{i+1}^-

Let us now consider

$$\mathbf{U}_i^{n+1} = \mathbf{U}_i^n + \frac{\Delta t^n}{\Delta x} \left(\mathbf{F}_{i+\frac{1}{2}}^- (\mathbf{U}_i^n, A_{i+1}^-, Q_{i+1}^n, \mathbf{Z}_i, \mathbf{Z}_{i+1}^-) - \mathbf{F}_{i-\frac{1}{2}}^+ (A_{i-1}^+, Q_{i-1}^n, \mathbf{U}_i^n, \mathbf{Z}_{i-1}^+, \mathbf{Z}_i) \right)$$

instead of the previous one :

$$\mathbf{U}_i^{n+1} = \mathbf{U}_i^n + \frac{\Delta t^n}{\Delta x} \left(\mathbf{F}_{i+\frac{1}{2}}^- (\mathbf{U}_i^n, A_{i+1}^n, Q_{i+1}^n, \mathbf{Z}_i, \mathbf{Z}_{i+1}^-) - \mathbf{F}_{i-\frac{1}{2}}^+ (A_{i-1}^n, Q_{i-1}^n, \mathbf{U}_i^n, \mathbf{Z}_{i-1}^-, \mathbf{Z}_i) \right)$$



DEFINITION OF THE NEW FLUXES : M-SCHEME

IDEAS : replace

- dynamic quantities \mathbf{U}_{i-1} and \mathbf{U}_{i+1} by stationary profiles \mathbf{U}_{i-1}^+ and \mathbf{U}_{i+1}^-
- sources terms \mathbf{Z}_{i-1} and \mathbf{Z}_{i+1} by stationary profiles \mathbf{Z}_{i-1}^+ and \mathbf{Z}_{i+1}^-

Let us now consider

$$\mathbf{U}_i^{n+1} = \mathbf{U}_i^n + \frac{\Delta t^n}{\Delta x} \left(\mathbf{F}_{i+\frac{1}{2}}^-(\mathbf{U}_i^n, A_{i+1}^-, Q_{i+1}^n, \mathbf{Z}_i, \mathbf{Z}_{i+1}^-) - \mathbf{F}_{i-\frac{1}{2}}^+(A_{i-1}^+, Q_{i-1}^n, \mathbf{U}_i^n, \mathbf{Z}_{i-1}^+, \mathbf{Z}_i) \right)$$

Then,

THEOREM

the numerical scheme is well-balanced.

PROOF

- the numerical flux is, by construction, consistent.

PROOF

- the numerical flux is, by construction, consistent.
- Let us assume that there exists n such that for every i :

$$Q_i^n = Q_0, \quad D(\mathbf{U}_i^n, \mathbf{Z}_i) = h_0.$$

PROOF

- the numerical flux is, by construction, consistent.
- Let us assume that there exists n such that for every i :

$$Q_i^n = Q_0, \quad D(\mathbf{U}_i^n, \mathbf{Z}_i) = h_0.$$

Then,

$$D(A_{i+1}^-, Q_{i+1}, \mathbf{Z}_i) = D(\mathbf{U}_{i+1}, \mathbf{Z}_{i+1}) = h_0, \quad \forall i$$

and especially, we have :

$$D(A_{i+1}^-, Q_{i+1}, \mathbf{Z}_i) = D(\mathbf{U}_i, \mathbf{Z}_i).$$

PROOF

- the numerical flux is, by construction, consistent.
- Let us assume that there exists n such that for every i :

$$Q_i^n = Q_0, \quad D(\mathbf{U}_i^n, \mathbf{Z}_i) = h_0.$$

Then,

$$D(A_{i+1}^-, Q_{i+1}, \mathbf{Z}_i) = D(\mathbf{U}_{i+1}, \mathbf{Z}_{i+1}) = h_0, \quad \forall i$$

and especially, we have :

$$D(A_{i+1}^-, Q_{i+1}, \mathbf{Z}_i) = D(\mathbf{U}_i, \mathbf{Z}_i).$$

The application $A \rightarrow D(A, Q, Z)$ being injective, provides $A_{i+1}^- = A_i$ and thus $\mathbf{Z}_{i+1}^- = \mathbf{Z}_i$ by construction. Similarly, we get $A_{i-1}^+ = A_i$ and $\mathbf{Z}_{i-1}^+ = \mathbf{Z}_i$.

PROOF

- the numerical flux is, by construction, consistent.
- Let us assume that there exists n such that for every i :

$$Q_i^n = Q_0, \quad D(\mathbf{U}_i^n, \mathbf{Z}_i) = h_0.$$

Then,

$$D(A_{i+1}^-, Q_{i+1}, \mathbf{Z}_i) = D(\mathbf{U}_{i+1}, \mathbf{Z}_{i+1}) = h_0, \quad \forall i$$

and especially, we have :

$$D(A_{i+1}^-, Q_{i+1}, \mathbf{Z}_i) = D(\mathbf{U}_i, \mathbf{Z}_i).$$

The application $A \rightarrow D(A, Q, Z)$ being injective, provides $A_{i+1}^- = A_i$ and thus $\mathbf{Z}_{i+1}^- = \mathbf{Z}_i$ by construction. Similarly, we get $A_{i-1}^+ = A_i$ and $\mathbf{Z}_{i-1}^+ = \mathbf{Z}_i$. Finally, since

$$\mathbf{F}_{i+\frac{1}{2}}^-(\mathbf{U}_i^n, \mathbf{U}_{i+1}^-, \mathbf{Z}_i, \mathbf{Z}_{i+1}^-) - \mathbf{F}_{i-\frac{1}{2}}^+(\mathbf{U}_{i-1}^+, \mathbf{U}_i^n, \mathbf{Z}_{i-1}^+, \mathbf{Z}_i) = 0,$$

we get $\forall l \geq n, \quad Q_i^{l+1} = Q_i^l := Q_0$.



NUMERICAL PROPERTIES

For instance, with the simplest χ function [ABP00],

$$\chi(\omega) = \frac{1}{2\sqrt{3}} \mathbb{1}_{[-\sqrt{3}, \sqrt{3}]}(\omega)$$

the following properties holds :

- Positivity of A (under a CFL condition),
- Conservativity of A ,
- Discrete equilibrium and,
- Natural treatment of drying and flooding area.

for example

and analytical expression of the numerical macroscopic fluxes.



E. Audusse and M-O. Bristeau and B. Perthame.

Kinetic schemes for Saint-Venant equations with source terms on unstructured grids.
INRIA Report RR3989, 2000.

1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model


2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results


3 CONCLUSION AND PERSPECTIVES

QUALITATIVE ANALYSIS OF CONVERGENCE

AND COMPARISON WITH THE WELL-BALANCED VFROE SCHEME




- upstream piezometric head 104 m



- downstream piezometric head :


CONVERGENCE

During unsteady flows $t = 100$ s



CONVERGENCE

Stationary $t = 500$ s



1 UNSTEADY MIXED FLOWS : PFS EQUATIONS (PRESSURIZED AND FREE SURFACE)

- Previous works
- Formal derivation of the free surface and pressurized model
- A coupling : the PFS-model

2 A FINITE VOLUME FRAMEWORK

- Kinetic Formulation and numerical scheme
- The χ function and well balanced scheme
 1. Classical scheme fails in presence of complex source terms
 2. An alternative toward a Well-Balanced scheme
- Numerical results

3 CONCLUSION AND PERSPECTIVES

CONCLUSION



Conservative and simple formulation :

→ easy implementation even if source terms are complex



The most of the properties of the continuous model are maintained at discrete level :

→ positivity of the water area

→ conservativity of the water area

→ discrete equilibrium maintained

CONCLUSION AND PERSPECTIVES



Conservative and simple formulation :

→ easy implementation even if source terms are complex



The most of the properties of the continuous model are maintained at discrete level :

→ positivity of the water area

→ conservativity of the water area

→ discrete equilibrium maintained

What about discrete entropy inequalities ?

→ same difficulties as for discrete balance (see [PhDErsoy] Chap. 2 for further details)

A dynamic background image showing a large splash of water with many droplets in the air, creating a sense of movement and freshness. The water is a clear, light blue color.

Thank you

Thank you

for your

for your

attention

attention

2+3 tane dis!!! 20 Mars 2011